

Scholl.
The Radioactivity Of Illinois Waters.



## THE RADIOACTIVITY OF ILLINOIS WATERS

BY

#### CLARENCE SCHOLL

B. S. University of Illinois, 1913

M.S. University of Illinois, 1914

## THESIS

Submitted in Partial Fulfillment of the Requirements for the

Degree of

DOCTOR OF PHILOSOPHY

IN CHEMISTRY

IN

THE GRADUATE SCHOOL

OF THE

UNIVERSITY OF ILLINOIS

1916




# 1916 Sch 59 UNIVERSITY OF ILLINOIS THE GRADUATE SCHOOL

May 6 Int 6

	,
I HEREBY RECOMMEND THAT THE THESIS PREP.	ARED UNDER MY SUPER-
VISION BYCLARENCE SCHOLL	
ENTITLED THE RADIOACTIVITY OF ILLINOIS	WATERS.
BE ACCEPTED AS FULFILLING THIS PART OF THE R.	EQUIREMENTS FOR THE
	~
DEGREE OF DOCTOR OF PHILOSOPHY	***************************************
$\sim$	
Odward (	Barlow.
	In Charge of Thesis
W. A. N &	4-3
	Head of Department
	•
Recommendation concurred in:*	
E. H. Hashburn	
51. 771	Committee
- D. C. Mac Junes	on
Joel a Sperry dans	Final Examination*
	1

\*Required for doctor's degree but not for master's.



## TABLE OF CONTENTS.

I.	Historical	1
III.	Methods of Detection and Measurement of Activity Photographic Method Luminous Screen Method Electrical Method Radioactive Standards Plan of Work	4 5 6 7 10
	Apparatus	
•	Electroscope for Gases Electroscope for Solids	12
VI.	Standardizing of Electroscopes	14
	Electroscope for Gases	15 17
VII.	Electroscope for Solids Separation of Emanation from Water	18
	Waters Examined	
V A A A 0	Test for Thorium Mineral Content Radioactivity Analyses Sources of Waters	19 19 19 20
IX.	Results	24
	Deep Rock Well Waters	25 25
	Drift Well Waters Lower Mississippian Waters	27
	Springs	27
	North of Ozark Uplift	28
	In Ozark Uplift	29
х.	Comparison with other American and European Waters	30
	Conclusions	34
XII.		35 38
XIII.	Biography	20



## TABLES.


II. IV. V. VI.	List of Radioactive Elements Relative Luminescence of Various Bodies Activities in a Uranium Mineral Standardizing of Electroscope for Gases (A) Standardizing of Electroscope for Gases (B) Standardizing of Electroscope for Solids Standardizing of Electroscope for Thorium Comparison of Radioactivity, Calcium, magnesium, and residue Decay of Activity of Water from Dixon Springs Radioactivity of American and European Waters	3 5 9 16 17 18 21 32
	and the second s	
	FIGURES.	
	r igo red.	
1. 2. 3. 4. 5. 6. 7.	Simple Electroscope for Solids Simple Electroscope for Gases Simple Electroscope for Solutions Electroscope for Solids Electroscope for Gases, Front View Electroscope for Gases, Side View Apparatus for Separating Emanation from Uraninite Apparatus for Separating Emanation from Water	40 40 40 41 41 41
	DT A MDG	
	PLATES.	
1.	Comparison of Decay of Activity of Water With Radium Emanation Dixon Spring No. 2	42
2.	Dixon Spring No. 3	43
3. 4.	Dixon Spring No. 4 Dixon Spring No. 7	44 45
5	Relation of Activity to Mineral Matter in Waters	4.0
5. 6.	Calcium in Waters from Deep Rock Wells Magnesium in Waters from Deep Rock Wells	46 47
7.	Calcium in Waters from Drift Wells	48
8.	Magnesium in Waters from Drift Wells Calcium plus Magnesium in Waters from Drift Wells	49 50
10.	Residue in Waters from Drift Wells	51
11.	Calcium in Waters from Lower Mississippian Residue in Waters from Lower Mississippian	52 53
13.	Calcium in Waters from Springs	54
14.	Residue in Waters from Springs	55

Digitized by the Internet Archive in 2013

#### THE RADIOACTIVITY OF ILLINOIS WATERS.

At the suggestion of J. J. Thomson who visited the United States in 1902 and who reported that the research men of the Cavendish Laboratory of London had separated a very active gas from a deep well water, Bumstead and Wheeler 26 investigated the waters of New Milford and New Haven. Connecticut. They found that these two waters contained active gases whose activity was six to eight times the normal air leak of an electroscope. Similar investigations made by other research men. 1,3,29,36,56,72,115, using European waters showed that the active gases occurred universally but varied in quantity in different localities. As there was no standard of activity at that time no quantitative measurements of activity were made. The investigators did, however, determine the period of decay of the active material, and found it to correspond in most cases to the decay period of radium emanation.

Boltwood 17 in 1904, and with Rutherford 19 in 1906, investigated the proportion of radium and uranium in radio-active minerals and found the ratio of radium to uranium to be constant, 3.4 x 10<sup>-7</sup> grams of radium per gram of uranium. Recently Lind and Whittemore 69 (1915) have confirmed this ratio. As the amount of radium emanation in equilibrium with radium is constant; the amount of radium emanation is, therefore, in a ratio to the amount of uranium. Boltwood 15




suggested that the quantity of radium emanation set free when a known weight of a natural uranium mineral is dissolved in a suitable reagent be taken as a standard of radioactivity.

Boltwood<sup>18</sup> (1905) first used his standard in investigating the activity of the very active thermal springs of Hot Springs, Arkansas. Boltwood's emanation standard was adopted by Moore and Schlundt in their investigations of the waters of Missouri<sup>82</sup> (1905), and the thermal waters of the Yellowstone National Park<sup>83</sup> (1909); by Shrader<sup>111</sup> in the investigation of waters near Williamstown, Massachusetts (1914); by Moore and Whittemore<sup>84</sup> (1914) in the investigation of Saratoga Springs, New York; by Ramsey<sup>91</sup> (1915) in the investigation of the waters of Indiana and Ohio; and by Perkins<sup>89</sup> (1915) in the investigation of the waters of Rhode Island.

The radium emanation to which the radioactivity of waters is due is formed by the decomposition of radium, which may or may not be present in the water. The emanation with or without radium but with other mineral salts is dissolved by the water in its passage through the ground.

Radium emanation is the sixth element in the list of active elements compiled by Rutherford. 97




List of radioactive elements.

Element	Radiation	Half life period
Uranium	$\alpha$	6 x 10 <sup>9</sup> years
Uranium X	8+4	24.6 days
Uranium Y	. β	1.5 days
Ionium	d	Greater than
Radium	at slow B	20,000 years 2000 years
Emanation	æ	3.85 days
Radium A	≪	3 min.
Radium B	B+r	26.8 min.
Radium Cl	d+B+r	19.5 min.
Radium Ca	$\boldsymbol{\beta}$	1.4 min.
Radium D	slow B	16.5 years
Radium E	B+~	5 days
Radium F	d	136 days

Radium salts are seldom found in natural waters.

Radium salts have been found in waters in the Tyrol<sup>7</sup> district of the Alps and in the Doughty Springs<sup>47</sup> of Colorado. Their absence in most natural waters is explained by the chemical properties<sup>113</sup> of the element. It is in the second group of Mendeljeff's periodic system as the highest member of the barium series. Therefore radium sulfate is even more insoluble than barium sulfate. Even radium chloride remains dissolved only in a solution strongly acidified with hydro-




chloric acid. Since many natural waters are alkaline and many contain large quantities of sulfate, radium salts can not be present in solution. If a ground water did dissolve some radium salts, the radium salts would be precipitated at once upon coming in contact with the chloride or sulfate ion. The large majority of waters therefore contain only emanation.

Methods of Detection and Measurement.

Three general methods have been employed for the determination of the presence of radioactive material.

- 1. The photographic method.
- 2. The luminous screen method.
- 3. The electrical method.
- extensively especially in the early measurements of activity. It depends on the darkening of a photographic plate when exposed to the action of the active substance. The method may be used with distinct advantage in studying the curvature of the path of the rays when under the influence of a magnetic or electric field. But it is open to many objections as a method for determining the quantity of active material present. The active material must be in the solid state of aggregation. A day's exposure is usually required to produce an appreciable darkening of the photographic film when the plate is exposed to a weak source of radiation. The darkening of a photo-




graphic plate can also be produced by many agents which do not give out radioactive rays. Hence special precautions are necessary when long exposures are required. The chief difficulty, however, lies in the inaccuracy of the measurements of the density of the photographic impression from which the intensity of the radiation must be calculated.

2. The luminous screen 28,35 method depends on the fact that when an alpha ray from an active material strikes a screen of a sensitive material such as barium platinocyanide, willemite, diamond, or zinc sulfide a short illumination appears. The amount of active material present can be calculated from the number of illuminations in a given time. The method has been used extensively but its application is limited on account of the small intensity of some of the illuminations. The luminosity produced in barium platinocyanide, willemite, and diamond is only of service in qualitative work. The relative luminosity of various substances is as follows:

Relative Luminescence of Various Bodies. 100

Substance	Without Screen	Through Black paper
Zinc blende	13.36	0.53
Barium platinocyanide	1.99	0.10
Diamond	1.14	0.01
Potassium uranium double sulfate	1.00	0.31
Calcium fluoride	0.30	0.01



The luminosity produced in zinc sulfide by alpha rays has proven invaluable in quantitative work. It affords a direct method of counting the number of alpha particles emitted from an active body. The activity of a solid substance can be determined by this method but it is not applicable to waters whose activity is due to gases.

on the property possessed by radioactive substances of ionizing gases; that is, positively and negatively charged particles are produced in the gas. The ionization is directly proportional to the number of rays emitted, directly proportional to the quantity of radioactive material, and directly proportional to the current of electricity which can pass through the gas. The strength of this current of electricity is the quantity that is usually determined. The maximum current produced when the gas is electrically saturated is always taken.

The strength of the current can be measured with a sensitive electrometer<sup>2</sup>, 25, 37,71. But in most cases since the material is slightly active, it is more convenient to use an electroscope. 17,63,125,126 The capacity of an electroscope is nearly constant, hence the average rate of movement of the leaves is directly proportional to the rate of discharging the system, to the amount of electricity passing through the gas, to the ionization of the gas, to the number of rays emitted, and to the amount of active material present. If a solid substance is placed between two horizontal plates, the lower




connected to the earth, the upper connected to the leaf system of an electroscope which is charged, (See figure 1) the activity can be directly determined by finding the rate of fall of the leaf. The fall of the leaf can be observed with a telemicroscope provided with a uniform scale in the eyepiece, the time being taken with a watch. The observed fall must be corrected by subtracting the natural leak of the apparatus when no radio-active material is present. An electroscope of this kind is especially suited for the measurement of activity caused by alpha rays.

A modification of this electroscope can be used to determine extremely small currents of electricity with accuracy. This modification first used by C. T. R. Wilson<sup>125</sup> in the study of the ionization of air, has the gold leaf attached to the upper plate which is vertical. The whole system of plate and leaf is then insulated within the containing vessel after charging. The charging is done by means of a movable wire which passes through the walls of the vessel and may be touched to the upper plate whenever desired. (See figure 2)

### Radioactive Standards.

The results obtained by one investigator should be comparable with the results obtained by another. One standard of radioactivity should be convertible into the terms of another standard. A great many measurements of the activity of spring and well waters have been made, but there is no




general comparison of the results of various investigators.

Many standards have been suggested, but only three are now in general use. These are the McCoy<sup>79,80</sup> urano-uranic oxide standard, the Boltwood equilibrium emanation<sup>16,19</sup> standard (the Curie)<sup>22</sup> and the C.G.S. absolute standard.

McCoy, Ashman, and Ross<sup>80</sup> have recently studied the relation between the McCoy urano-uranic oxide standard and the C.G.S. unit by using uniform layers of especially prepared oxide<sup>79</sup>. They found the ionization currents due to the alpha rays from a thick film of urano-uranic oxide to be 5.79 x 10<sup>-13</sup> amperes or 1.737<sup>-3</sup> C.G.S. electrostatic units per square centimeter. This value is constant and capable of being reproduced. The specific activity of uranium<sup>78</sup> defined as the total ionization current from one gram of uranium, when all the radiation is absorbed in the air, is 796 McCoy units. The total ionization current from one gram of uranium free from its products is then 1.38 C.G.S. electrostatic units.

Rutherford<sup>99</sup> has shown that one gram of uranium emits  $2.37 \times 10^4$  alpha particles per second. Each particle has a range of 2.50 cm. and produces a total of  $1.26 \times 10^5$  ions. Each of these ions<sup>98</sup> has an elementary charge of electricity of  $4.65 \times 10^{-10}$  C.G.S. electrostatic units. Thus one gram of uranium is equivalent to  $2.37 \times 10^4 \times 1.26 \times 10^5 \times 4.65 \times 10^{-10} = 1.38$  C.G.S. electrostatic units. This agrees with the results above.

Boltwood<sup>20</sup> has shown that if the activity of uranium



free from its product be taken as 1.00, the relative values of the activities, due to alpha rays of the different elements in equilibrium in a uranium mineral are as follows:


Uranium	1.00
Ionium	.34
Radium	.45
Radium emanation	.54
Radium A	.62
Radium B	.04
Radium C	.91
Radium F (Polonium)	.46
Actinium and its products	.28

Total activity 4.64 x Uranium

In the determination of the activity of a sample of uraninite by means of the emanation method we separate an activity equivalent to that of radium emanation or 0.54 of the activity of the uranium present. But the decay of radium A.B., and C., are so rapid that in the determination we measure not only the effect of the radium emanation but also the effect of radium A.B., and C., which are produced in the decay of emanation. The effect of radium F (polonium) is small and can be neglected. The sum of these activities will be 0.54 + 0.62 + 0.04 + 0.91 = 2.11 times that due to uranium free from its products, if all the activity is absorbed in air.

Hence 1.38 x 2.11 = 2.90 C.G.S. Electrostatic units is the total equivalent of one gram of uranium in uraninite, if the emanation is calculated at its maximum activity.

By using Duane and Laborde's 32 formula (the relation of maximum current to the current obtained in any electroscope)



which is

$$I_0 = \frac{I}{(1-0.57s)}$$

(I is the electrical current in E.S.U. in an electroscope with a surface S and a volume V. Io is the true equivalent in E.S.U.) we get

$$I = I_0 (1-0.57 \frac{s}{v})$$

Substituting the values of S and V for the gas electroscopes, we get

$$I = 2.90 (1-0.57 \frac{36}{27})$$

$$I = 0.696 E.S.U.$$


The activity of one gram uranium equals 0.696 E.S.U. (C.G.S. system).

This factor was used in changing data from the uraninite standard to electrostatic unit standard.

#### Plan of Work.

The purpose of this investigation was to determine the radioactivity of Illinois waters quantitatively and then to study the relations, if any, between the radioactivity and the mineral constituents dissolved in the water in respect to the geographical and geological locations from which the waters come.

The electrical method of measuring radioactivity was adopted for use in our investigations. At first an electroscope designed according to the specifications of some European




investigators<sup>39</sup> (See figure 3) was used. When tested with uraninite it was found to be unreliable for small quantitative measurements. A modification of an electroscope design by C. T. R. Wilson, <sup>125</sup> was tested and found satisfactory for the measurement of radioactivity of gases. An electroscope with an ordinary leaf system was adopted for testing the activity of solids.

Some of the waters were analyzed in the field, samples of others were collected, sealed, and shipped to the laboratory where they were analyzed immediately. The results of the analyses made in the laboratory were corrected for the decay of activity by means of the formula  $I_0 = I_t e^{-rt}$ .  $I_0$  is the initial activity;  $I_t$  is the observed activity at the time of making the analysis, t hours after the water was collected. r is the radioactive constant  $^{102}$  and has a value of .0075 when t is expressed in hours, or 0.1800 when t is expressed in days.

Whenever the presence of radium salts was suspected, the water was evaporated to about 100 cc., acidified with HCl, sealed, kept for thirty days, in order to allow the emanation to again reach a maximum, and again tested. The activity if any, was due to the radium present in the original sample.

Samples of sediment, when occurring in the waters were analyzed in a similar manner but none were found to be radioactive.

The waters were analyzed for their mineral constituents by the method advocated by the American Public Health



Association<sup>6</sup> and the Illinois State Water Survey. <sup>58</sup>

## Apparatus.

Electroscope for determination of gases.

The electroscope, constructed by the Central Scientific Company is a modification of Boltwood's modification of Wilson's electroscope. 125 It consists of a cylinder 8 cm. long and 15 cm. in diameter, fitted at each end with a piece of plate glass. The side of the cylinder is securely fastened to a wooden base by means of an iron stand (A) four inches high. A short wide glass tube (B) covers a hole in the top of the cylinder. A brass cap (C) surmounts the glass tube. A short brass rod (D) is screwed into the cap. A piece of amber, (E) which is screwed on the lower end of rod (D), supports a gold or aluminium leaf (F) and plate (H). The amber insulates the leaf and plate within the cylinder.

The device for charging is a special feature. An arm (K) is fastened on the brass rod (D) and supports a soft iron wire (J) which extends below the amber insulator but does not touch it. The leaf is charged to the same potential as the brass cap above, by bringing a magnet near the glass and forcing the wire against the leaf plate. Two air tight stopcocks (S), one at the top and one at the bottom are for the admission of gases. All the joints are made airtight by sealing with wax and rosin. An aluminium leaf (5 x 50 mm) was used rather than a gold leaf which gave trouble continually.




It was fastened to the plate by placing a streak of glue across the upper part of the plate and then pressing the leaf firmly against it. The original aluminium leaves have withstood transportation by rail to various parts of the state and are still in good condition.

The electroscope was charged by the following method:
The iron wire (J) was forced with a magnet against the leaf
plate. A charged vulcanite rod was brought near the cap until
the desired potential was obtained. The iron wire (J) was
allowed to swing free by removing the magnet. The vulcanite
rod was withdrawn. The cap was earthed for an instant. Thus
the leaf, which was insulated within the cylinder, was charged
at the desired potential.

A tele-microscope, an eye piece of which contained a scale twelve millimeters long with each millimeter divided into ten divisions, was used to determine the rate of fall of the leaf. A stop watch recording fifths of a second, was used to determine the time interval.

Two U tubes, one containing phosphoric oxide (P2O<sub>5</sub>), the other containing calcium chloride (CaCl<sub>2</sub>), was always connected in series with the electroscope, when evacuating or adding gases to the electroscope. The phosphoric oxide (P2O<sub>5</sub>) tube was between the electroscope and the calcium chloride tube.




### Electroscope for Solids.

The electroscope for measuring the radioactivity of solids, obtained from E. H. Sargent of Chicago, consisted of a cubical metal box (4 1/2 in. cube) fitted on two opposite sides with glass plates which could be raised or lowered. An amber ring supported and insulated a leaf and brass ball above from the center of the top. These with a leaf plate and rod connecting the brass ball above made up the electric carrying portion of the electroscope. A small copper tray 4 x 4 x 1/2 in. held the solid material when it was inserted in the box for the determination. No precautions were taken for drying the material.

## Standardizing of Electroscopes.

The methods of measuring radioactivity give relative quantitative values. The activity of some substance is taken, as the fundamental unit and the activities of other substances are compared with it. Fundamental units are the Mache unit, the Curie unit, and uranium. The amount of radium in one gram of uranium in uranium ores as found by Boltwood 19,21 and Rutherford 101 and later Strutt 116 and McCoy 77, is always 3.4 x 10-7 grams. If the emanation from a weighed sample of uranium mineral whose content of uranium is known from a chemical analysis, is used, we can calculate the radium equivalent of the activity. Thus if we use one gram of mineral containing 25% of uranium then the fall of the leaf of the electroscope would correspond to 3.4 x 10-7 x .25 = 0.85 x 10-7



grams of radium. Or if expressed in grams of radium per space per minute we have  $\frac{3.4 \times 10^{-7} \times .25}{\text{no. of spaces fallen in 1 min.}}$  = X grams

of radium in uranium mineral per space fall per minute. A "curie" 20 is the amount of emanation in equilibrium with one gram of radium. Hence the activity obtained from X grams of radium is X Curies of emanation.

Standardizing Electroscope for Gases.

Procedure: A small weighed quantity of the standard sample of uraninite containing 43.6% uranium was placed in a flask (A) (Fig. 7) of about 100cc. capacity. 10.0 mg. were usually taken as this quantity furnished a convenient rate of fall of the leaf. This flask was closed with a rubber stopper having two holes. A separatory funnel was fitted in one hole, an upright condenser in the other. The condenser is connected by a glass tube and stopcock to another flask (B) also fitted with a stopper having two holes. Through one is the connection to the condenser and the other a glass tube with a stopcock (C). The whole apparatus having been made air-tight was evacuated by means of a pump connected to the stopcock (C). A little dilute nitric acid was added to the uraninite in the flask (A). It was then heated to the boiling point and boiled for fifteen minutes. The acid and water rising as vapor condensed in the condenser and returned to the flask. After boiling fifteen minutes distilled water free from emanation was allowed to run into the apparatus through the separatory funnel until the



mark (D) was reached. Stopcock (E) was then closed. The emanation with other gases was now in flask (B) under a fraction of an atmosphere pressure. They were introduced into the partially exhausted electroscope and the rate of fall of the leaf determined after from 3 to 3 1/2 hours. The fall of the leaf was corrected by subtracting the normal air leak of the electroscope when the gas in the electroscope is free from emanation. The correction is always small amounting to .003 division per minute for electroscope (A). The rate of fall was always taken when the leaf was forming an angle of less than 30° with the plate.

The electroscopes were standardized at frequent intervals. See tables II and III.

Table II. Standardization of Electroscope (A).

Date	Mineral used (grams)	Divisions fall per min.	ne	per divisions r minute Ra.g.x 10-10
Oct. 23, 1914	.0299	15.80	8.28	2.81
Oct. 26, 1914	.0301	16.08	8.12	2.76
Dec. 4, 1914	.0253	18.18	6.06	2.06
Dec. 5, 1914	.0069	4.92	6.11	2.08
Feb. 24, 1915	.0078	5.50	6.50	2.21
Sept. 25, 1915	.0078	5.50	6.50	2.21
Dec. 13, 1915	.0074	2.14	15.1 (a)	5.13
Dec. 14, 1915	.0113	3.17	15.2	5.17
Jan. 7, 1916	.0159	10.0	6.93(b)	2.36
Jan. 8, 1916	.0082	5.14	6.95	2.36

<sup>(</sup>a) The aluminium leaf was shortened to about one-half its original length.

<sup>(</sup>b) A new leaf was placed in the electroscope.




Table III. Standardization of Electroscope (B).

	Mineral used (grams)	Divisions fall per min.	min	divisions per ute Ra.g. x 10-10
Oct. 23, 1914 Oct. 26, 1914 Dec. 4, 1914 Dec. 5, 1914 Sept. 25, 1915 Dec. 13, 1915 Dec. 14, 1915	.0342 .0340 .0204 .0125 .0086 .0105	18.28 18.28 9.92 6.70 4.55 6.00 5.40	8.16 8.14 8.86 8.13 8.24 7.68 7.64	2.77 2.77 3.01 2.76 2.80 2.61 2.59
Dec. 13, 1915	.0105	6.00	7.68	2.61

Standardizing Electroscope for Solids.

Procedure for Uranium. A small weighed quantity

(0.1 gram) of the original uraninite was dissolved in a small

quantity of nitric acid and evaporated to dryness in a

porcelain dish. The residue was taken up with a small quantity

of water, transferred to a copper plate and evaporated to

dryness. This plate was then inserted into the electroscope

and the rate of fall of the leaf determined. (See Table IV).


The rate of the normal leak which was obtained in exactly the

same manner but without the uraninite was subtracted.

Table IV. Standardization of the Electroscope for Uranium.

Date	Mineral	Divis. f	fall	per 1	min.	Uranium,	grams
Nov. 19, 1914	0.100 gram	7	7.06			Uranium, per divis	min.

Thus a fall of the leaf of one millimeter per minute, represents 6.2 milligrams of uranium in uraninite.



Procedure for Thorium. Thorium sulfate and nitrate were substituted for the uraninite, using the same procedure as for Uranium. (See Table V)


Table V. - Standardization of Electroscope for Thorium.

Date	Thorium grams	Divisions fall per min.	Thorium per divis. per min
Dec. 8, 1914	0.274 as sulfate	3.47	•0 <b>7</b> 8
Jan. 17, 1916	0.1124 as nitrate +0.5 g. NaCl	1.46	.077
Jan. 27, 1916	0.0196 as nitrate +0.2 g. NaCl	0.23	.085
Jan. 20, 1916	0.0196 as nitrate	.97	.0202

Separation of the Emanation from Water.

The sample of water to be analyzed for radioactivity was collected in a round bottom-flask holding about 1200 cc.

A liter was taken except when the water was very active in which case only 500 cc. was taken. Great care was exercised in getting a representative sample of the water. The flask was immediately closed with a two-hole stopper fitted with two glass tubes with two rubber tubes with pinch cocks. (See Figure 8) The flask was then connected to an upright condenser (B) and flask (C). The condenser (B) and flask (C) were evacuated with the pinch cock (D) closed. The pinch cock (D) was opened and the water in flask A was heated to boiling and boiled vigorously for about 20 minutes. Water free from emanation was then allowed to run in through the stopcock (E), as in the process of standardization. The emanation with



the other gases were then transferred to an electroscope and their activity determined.

Test for Thorium.

After the expulsion of radium emanation in the determination of radioactivity the samples of water were evaporated to dryness. The residues were taken up in a small quantity of hydrochloric acid (HCl) and after transferring to small plates (4 in. diameter and 1/4 in. deep) were again evaporated to dryness. The activities of the residues on these plates were then determined in the electroscope for solids. In none of the waters tested was any thorium found.


Portions of the deposits found at some of the springs were tested for activity in the same manner. There was no evidence of thorium.

Mineral Content of the Waters Examined.

The records of the State Water Survey, of the mineral content of waters of the state were consulted and typical waters were selected for the radioactive determinations. In some cases the recorded analyses were used in our comparisons and in others new analyses were made.

Radioactivity Analyses.

Gas was found escaping from only one water (Alton mineral spring). It was evolved at a rate of about 3 cc. a minute. No radium or thorium emanation was found in the gas.



Deposits were found only at the Dixon springs of the Ozark uplift. No radium or thorium was found in the deposits.


One hundred and thirty determinations of radioactivity of natural waters were made. Thirty-seven determinations of the radioactivity of residues sealed for thirty days were made. Twenty-two specimens of the mineral residues were tested for thorium. No thorium was detected in either the residues or waters. Excluding negative and doubtful results, the analyses of sixty-eight waters whose activity and whose mineral constituents are known are compared. (See table VI)

Sources of the Waters Examined.

Natural waters may be classified according to their physical and chemical properties 49 or according to the geological strata from which they come. Classification by physical and chemical properties, as for example Peale's 50 classification which was modified by Haywood 51, have been tried, but have not been found advantageous. No direct relation between the radioactivity and the classes of water indicated has been found.

Geologically Illinois waters fall into four large groups. (1) the waters from deep rock in the northern part of the state including waters from the Potsdam and St. Peter sandstones, the Trenton Galena formation, and the lower magnesium limestone.


(2) The waters from the drift, including those




# Table VI.

Comparison of Radioactivity, Calcium, Magnesium, and Residue.


	-21-	
E.S. U.	0400000400H0FF00000044	23.1
Radioactivity n Radium E. 10-10g. 10	タアらてよよりアンジの900000047001 2	1.12
Drenjum 10-48.		0 0 0 0
Rock Wells	16293 21884. 21884. 3364. 3364. 3364. 1070. 1070. 10999. 326. 326. 326. 327. 327. 327. 327. 327. 327. 327. 327	486.8
Magnesium Mg from Deep R	1884 4 8 4 6 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	888 8.38 8.4
Calcium Ca Waters		53.2
Depth Feet.	40088048   8348   90   91   9	156
Location	Alton Carbondale Carbondale Elgin Blgin Blgin Harvey Ottawa Ottawa Ottawa Ottawa Ottawa Ottawa Ottawa Streator	Bloomington Bloomington
Date	8008 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	2/26/16
Leb.No.	229223 24095 24095 23110 23110 23110 231110 231110 231110 231110 231110 231110 231110 231110 231110	14278
No	ことなるものでののこれなからりのこれ こころのものできるとののこれない。	22.24



		-22-	
	E.S.U.	8 8 1 1 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	
	Radiosct Radium 10-10g.	1000041400414000111 1001400 0000014000000000000000000000000	)
	Uranium 10-4g.	4000100440000000B0014000400000010014400000000B001400000000001004500000000000B0041040	•
	Residue	1 4 4 6 6 6 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
. (cont'd)	Magnesium Mg	0 1 4 0 4 0 7 4 4 4 4 6 0 2 0 1 0 2 0 1 0 2 0 1 0 2 0 1 0 0 0 1 0 0 0 0	2
Table VI	Calcium	######################################	•
	Depth Feet	1 11 113 17311	)
	Location	Carrier Mills Champaign Champaign Champaign Elgin Harrisburg Homer Homer Homer Joliet Joliet Joliet Joliet Joliet Joliet Joliet Lones Homer Home	nimom
	Date	200001	10/ 50/ 10
	Lab.No.	10605 1445044 3164445 3174846 3174846 317886 31886 3189 3168 31	oceoc coeoc
	No.	8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	311



E.S.U.	172 602 7.45 7.45 7.88 0.00 1.00	8441438 4454949 4454968
Radioactiv Radium 10-10g	82.00 8.00 8.00 8.00 8.00 8.00 8.00 8.00	1.00 1.00 1.00 1.00 1.00
Ru Urenium 10-4g.	481 881 88. 1.98 0.51 0.51	<b>88998899</b>
Residue	22222222222222222222222222222222222222	2610.1 1202.6 3623. 3276.7 1570. 477.5
Magnesium   Mg   K Uplift	1 1 1 1 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0	203.0 50.9 42.2 105.0 21.7 49.9
alcium Ca of Oza	41.600 84.1.600 84.1.600	North of 19.1 02.8 02.0 52.9 55.0
Depth Feet ng Water	-463	ng Water
Location	Creal Springs Dixon Spring Dixon Spring Dixon Spring Dixon Spring Dixon Spring	Spri It. Vernon It. Vernon Itawa Itawa Peru Faukegan
Date	12/2/15 CT 10/27/15 D1 10/27/15 D1 10/27/15 D1 12/16/15 D1 12/16/15 D1	10/28/15 Mt 2/28/15 Mt 2/25/16 Ot 2/25/16 Ot 2/25/16 Pe 2/19/15 Wa
Lab. No.	21943 21687 23106 23107 21688 21789	8106 23146 31110 31137 23733 29923
No.	000000000000000000000000000000000000000	0000000 0040000 000000



occurring in glacial drift, alluvial drift, and in loess.

- (3) The waters from the lower Mississippian, including the deep well waters south of the Ozark uplift.
- (4) The waters from the Ozark uplift, mainly springs, occurring among the Ozark foot hills of southern Illinois.


The radioactivity of the waters of Illinois varies with the geological formation, hence in the discussion they are considered according to these four groups.

### Results.

The activity of the sixty-eight waters, expressed in terms of uranium, radium, and electrostatic unit standards, are compared according to the four geological groups in which the waters are classified, with calcium, magnesium, and residue. (See table VI) No relation exists between the activity and the other mineral constituents, so that data concerning them are omitted.

The waters from deep rock wells (group 1) have a uniform activity but varying amounts of mineral constituents. The waters from drift wells (group 2) vary both in activity and mineral constituents. The waters from the lower Mississippian (group 3) vary in activity but have a uniform amount of mineral matter.

The spring waters (group 4) can be divided in two smaller groups. One with constant activity and varying mineral matter; the others with constant mineral matter and varying activity.




Group 1. Deep Rock Well Waters.

The activities of twenty-one waters from deep rock wells varies between 0.5 and 1.5 x 10-10 grams radium per liter. The largest number, however, have an activity of approximately 1.  $\times$  10<sup>-10</sup> g. radium per liter. These waters of quite uniform activity vary widely in mineral constituents for the calcium varies between 8 and 360 parts per million, the magnesium varies between 7 and 187 parts per million, the residue varies between 364 and 16,300 parts per million. A water (11, Peru) with a mineral content, of calcium 51.5 parts per million, of magnesium 10.5 parts per million, and of residue 746 parts per million has an activity of 1.05 x 10<sup>-10</sup> g. radium per liter, while another water (1. Alton) with a much higher mineral content of calcium 358.4 parts per million, of magnesium 186.8 parts per million, and of residue 16293.5 parts per million has an activity of 0.95 x 10<sup>-10</sup> g. radium per liter. an activity practically the same as that of the first water. Hence there appears to be no relation between the activity of these waters and the mineral constituents. (See plates 5 and 6).

# Group 2. Drift Well Waters.

The activities of twenty-six waters from drift wells vary between 0.5 and 5.7 x 10-10 g. radium per liter. These waters of varying activity, vary in mineral constituents for the calcium varies between 42 and 395 parts per million, the magnesium varies between 14 and 282 parts per million, the



residues vary between 327 and 2647 parts per million. The activity increases with an increase in mineral constituents.

A water (38, Rossville) of the lowest mineral content, calcium 57.5 parts per million, magnesium 42.9 parts per million, and residue 356.6 parts per million has a low activity, .54 x 10<sup>-10</sup>g. radium per liter, while another water, (37, Joliet) of the highest mineral content, calcium 394.4 parts per million, magnesium 281.5 parts per million, and residue 2647.4 parts per million has the highest activity, 6.36 x 10<sup>-10</sup> g. radium per liter. The activities of the two waters are in the same ratio as the like mineral constituents. (See plates 7, 8, 9, 10).


In many waters the relations approach quantitative results. The relation between the activity and calcium in the majority of the waters examined is 56 parts per million of calcium for every 1.  $\times$  10<sup>-10</sup> g. radium. (See plate 7).

The relation between the activity and magnesium in the majority of the waters examined is 44 parts per million magnesium for each 1.  $\times$  10<sup>-10</sup> g. radium. (See plate 8).

By adding the calcium and magnesium we get in the majority of waters examined 100 parts per million of calcium and magnesium for each 1.  $\times$  10<sup>-10</sup> g. radium. (See plate 9).

The relation between activity and residue in the majority of the waters examined is 400 parts per million residue for each 1.  $\times$  10<sup>-10</sup> g. radium. (See plate 10).

No other relation between the activity and mineral constituents were found. We also found no relation between the activity and the depth of the well.



Group 3. Lower Mississippian Waters.

The activities of seven waters from the lower Mississippian vary between 0.5 and 4.5 x 10-10 grams of radium per liter, a variation of 1 to 9. These waters of varying activity have quite uniform mineral constituents, for the calcium varies from 45 to 67 parts per million, a variation of only 1 to 1.5, the magnesium varies from 13 to 21 parts per million, a variation of only 1 to 1.7. the residues vary from 266 to 643 parts per million, a variation of only 1 to 2.4. The variation of the residues is even less if the sodium chloride is subtracted. (See plate 12). A water (50, Cairo) with a mineral content of calcium 46.1 parts per million, of magnesium 13.0 parts per million, and of residue 349 parts per million (residue minus sodium chloride equals 200 parts per million) has the lowest activity of 0.49 x 10<sup>-10</sup> g. radium per liter while another water (52, Cairo) with practically the same mineral content, of calcium 52.9 parts per million, of magnesium 13.8 parts per million, and of residue 435.6 parts per million (residue minus sodium chloride equals 224 parts per million) has the highest activity of 4.42 x 10-10 g. radium per liter, an activity nine times that of the first water. Hence there appears to be no relation between the activity of these waters and the mineral constituents. (See plates 11 and 12).

# Group 4. Springs.


The activities of fourteen spring waters vary between 0.8 and  $29.3 \times 10^{-10}$  g. of radium per liter. These waters of



varying activity have varying mineral constituents for the calcium varies between 3 and 319 parts per million, the magnesium between 0.5 and 203 parts per million, and the residues between 98 to 2610 parts per million. However, the waters can be divided into two groups, one group including the springs north of the Ozark uplift resembles the waters from deep rock wells having constant activity and variable mineral content, while the other includes the springs in the Ozark uplift and has variable activity and variable mineral content.

Springs North of Ozark Uplift.

The activities of seven springs north of the Ozark uplift vary between .7 and 1.7 x 10<sup>-10</sup> g. radium per liter, a variation of 1 to 2.4. These waters of quite uniform activity vary widely in mineral constituents for the calcium varies between 95 and 319 parts per million, a variation of 1 to 3.3, the magnesium varies between 23 and 203, parts per million, a variation of 1 to 9, and the residue varies between 533 and 3623 parts per million, a variation of 1 to 7. (See plates 13 and 14). A water (66, Peru) of low mineral content of calcium, 52.3 parts per million, of magnesium 21.7 parts per million, and of residue 1570 parts per million, has an activity of 0.91 x 10<sup>-10</sup> g. radium per liter, while another water (65, Ottawa) of much higher mineral content, of calcium 319.0 parts per million, of magnesium 105.0 parts per million, and of residue 3277 parts per million, has an activity of 0.78 x 10<sup>-10</sup> g. radium per



liter, which is slight/lower. Hence there appears to be no specific relation between the activity of these waters and the mineral constituents.

Springs of the Ozark Uplift.

The activities of seven springs in the Ozark uplift vary between 1.4 and 29.3 x 10-10 g. radium per liter, a variation of 1 to 21. These waters of very widely varying activity vary in mineral constituents for the calcium varies between 3 and 41 parts per million, a variation of 1 to 13.7, the magnesium between 0.5 and 18 parts per million, a variation of 1 to 36, the residue between 63 and 711 parts per million, a variation of 1 to 11.3. No uniform relation exists, however, between the activity and mineral constituents for the water highest in activity (29.3 x 10-10 g. radium per liter Dixon Spring No. 2. (57)) has an average amount of mineral matter, 26.4 parts per million of calcium, 14.1 parts per million of magnesium, and 232.9 parts per million of residue; the water highest in mineral matter, 41.2 parts per million calcium, 18.2 parts per million magnesium, and 306 parts per million residue, has a medium activity of 6.19 x 10<sup>-10</sup> g. radium per liter (Dixon Spring No. 1 (56)); the water lowest in activity (1.36  $\times$  10<sup>-10</sup> g. radium per liter for Dixon Spring No. 4 (59)) has a rather low mineral matter, 28.9 parts per million of calcium, 14.2 parts per million of magnesium and 261 parts per million of residue; while the water lowest in mineral matter, 2.9 parts



per million of calcium, 0.5 parts per million of magnesium, and 98.1 parts per million of residue, has a medium activity of  $4.42 \times 10^{-10}$  g. radium per liter (Dixon Spring No. 9 (61)). As both the mineral content and the activity is variable there appears to be no relation between the activity of these waters and the mineral constituents. (See plates 13 and 14).

Some of the springs of the Ozark region have the highest activities of any waters in the state, (29.3 x 10<sup>-10</sup> g.radium per liter in Dixon Spring No. 2, 22.8 x 10<sup>-10</sup> g. radium per liter in Dixon Spring No. 7). Careful search was made for thorium and uranium but none were found. The decay of the activity (Table VII) from four springs were determined during a period of nineteen days and found to be the same as that for radium emanation amounting to 3.85 days per half period. (Plates 1, 2, 3. and 4).

Comparison with other American and European Waters.

The activities of typical waters from various localities in America and Europe vary between 100 x 10<sup>-10</sup> g. radium per liter and zero. (See table VIII). The most active waters are found in localities where uranium deposits occur. (Colorado, Tyrol, Bohemia, etc.) No traces of uranium deposits have been found in Illinois. Next to the waters from uranium regions the imperial spring at Hot Springs, Arkansas, is the most having a radioactivity active in the United States amounting to 90.5 x 10 g. of radium per liter (266 x 10<sup>-4</sup> grams uranium). Two springs at Arlington, Rhode Island, are next with activities of 58 and




Table VII.

Decay of Activity of Water from Dixon Springs.

	Tin	ne	Activity	(10 <sup>-4</sup> g.	Ur) of Spring.	
			No. 2	No. 3	No. 4	No. 7
1.	1	hr.	2.58	2.80	2.05	***
2.	2	hrs.	2.58	3.51	2.65	
3.	3	hrs.	2.68		2.73	30.4
4.	5	hrs.	2.58		2.81	
5.	6	hrs.		3.25	2.81	
6.	18	hrs.			2.46	24.0
7.	24	hrs.	2.27	2.80	2.05	23.0
8	. 2	days	1.79			17.6
9.		days	100 dia 40 TID	1.55	1.31	
10.		days	1.26		60 top on top	11.4
11.		days	0.82	1.24	.82	
12.		days	0.18	.43	•33	
13.		days	0.12			
14		days	0.10	.33	• 30	0.60

47 x 10<sup>-10</sup> g. radium per liter. Dixon Spring No. 2 in this state is next with an activity of 29.3 x 10<sup>-10</sup> g. radium per liter. Several waters of high activity have been found in Germany and Switzerland. They are comparable with the highest waters in the United States. Other waters of Illinois vary in activity between the activity of Dixon Spring No. 2 and zero.


Several of the waters of Illinois have an activity as high as that of some waters for which medicinal value is claimed.

•

## Table VIII.

# Radioactivity of American and European Waters.

		7
E.	S.U. x 10	)-3
Austria, Tyrols, Froy Magnesium Springs	51.0	(7)
Austria, Tyrols, Froy Iron Springs	11.0	
Austria, Tyrols, Froy Sulphur Springs	4.5	
Italy, Naples, Near Hassler Hotel	2.7	(39)
Italy, Naples, Appolo Water	1.5	
France, Voges, Bain les Bains	16.0	(29)
France, Vichy, Chomel Spring	4.6	
France, Bagnoles de L'Orne	3.3	
France, Luxeuil, Grand Bain	2.3	
Germany, Gastein	149.0	(39)
Germany, Baden Baden Buttquells	126.0	
Germany, Baden Baden Freidrichsquelle	6.7	
Germany, Karlsbad Eisenquelle	47.0	
Germany, Karlsbad Felsenquelle	5.3	
Germany, Wildbad	1.8	(117)
Germany, Wiesbaden Koch Brunnen	2.3	(48)
Germany, Karlsbad Muhl Brunnen	31.5	(74)
Russia, Caucausus, Essentuky No. 6.	8.6	(81)
Russia, Caucasus, Batalinsky	1.5	, ,
Sweden, Uppsala Slottskallan	4.29	(112)
Sweden, Uppsala Bourbrum	3.77	(,
Sweden, Stockholm Birjerjarlsg No. 120	35.68	
Sweden, Medevi Höghum	6.38	
Switzerland, St. Joachimstahl	185.0	(74)
Switzerland, Rothenbrunnen	0.81	(109)
Switzerland, Disentis	46.7	(200)
Switzerland, Andeer	3.26	
Uranium		
10-4g.		
Arkansas, Hot Springs, Imperial Springs 266.0		(18)
Arkansas, Hot Springs, Twin springs 65.4		(10)
Arkansas, Hot Springs, Arsenic spring 23.9		
Indiana, Bloomington, city water	0.27	(91)
Indiana, Bloomington, University water	0.45	(-1)
Massachusetts, Williamstown, Sand spring	1.21	(111)
Massachusetts, Williamstown, Wampanoag	2.1	( /
Massachusetts, Williamstown, Rich spring	0.1	
Massachusetts, Williamstown, Sherman spring	0.4	
Massachusetts, Williamstown, Cold spring	0.1	
Missouri, Columbia, University well 1.68		(82)
Missouri, Sweet Springs, Sweet springs 23.7		(02)
Missouri, Fayette, Boonlick springs 4.6		
Missouri, Kansas City, Lake spring 48.2		
New York, Saratoga, Emperor	0.70	(84)
New York, Saratoga, Crystal rock	8.80	(04)
Ohio, Oxford	0.70	(91)
On a contract to the contract	0.10	(01)



	Uranium 10-4g.		E.S.U. 10-4	
Rhode Island, Arlington, Spring Rhode Island, Arlington, Spring Rhode Island, Providence, Rhode Island, East Providence		57.93 46.71 10.33 1.18		(89)
Yellowstone National Park Mammouth Hot Springs Devil's Ink Pot Realgar Springs Nymph Springs		14.4 0.23 4.0 2.6	0.4 7.4	(83)
Illinois Cairo Creal Springs, No. 3 Dixon Springs, No. 2 Dixon Springs, No. 7 Homer Park Joliet, Well Mt. Vernon, Spring	86.1 67.0	2.86	17.2 60.2 46.6 5.8 8.0	
Sea Water	98 to 98	0.0003		(64)



#### CONCLUSION

The activity of the waters from deep rock wells is low and constant.

The activity of the waters from the drift is low, but varies with the calcium, magnesium, and residue.

The activity of the waters from the lower Mississippian low and there is no relation to the mineral content.

The activity of the spring waters of the Ozark uplift is the highest in the state. There is no relation with the mineral content. The spring waters north of the Ozark uplift have a low and constant activity and closely resemble the waters of the deep rock wells.

The activity of the waters of Illinois bears no relation to the depth of the well.

The activity is due to radium emanation. In no case was uranium or thorium found.

The activity of Illinois waters is comparable with the activity of other waters of the United States and Europe.

While the most active waters of the state are not as as active/the most active waters in the United States, the activity of some Illinois waters is as high as that of some waters for which medicinal value is claimed.


M.A . 0.5 at sill dille

#### BIBLIOGRAPHY

```
Adams, Phil. Mag., 8, 563 (1903).
          Allen, Phil. Mag., 14, 742 (1907).
          Allen and Blythswood, Nature, 68, 343 (1903).
  3.
                                                      Ibid., 69, 247 (1904).
  4. Anon, Chem. News, 99, 45 (1909).
5. Anon, Pharm. Zentr., 52, 1149 (1912).
  6. A.P.H.A., Standard Methods, p. 65, (1912).
  7. Bamberger, Monatsch, 29, 317 (1908).
8. Bamberger, Monatsch, 29, 1131 (1909).
9. Bamberger and Kruse, Monatsch, 31, 221 (1911).
10. Bartow, Univ. Ill. Bull., 6, No. 3, p. 22.
11. Beaujeau, Comp. Rend., 153, 944 (1912).
12. Benndorf and Wellik, Mitt. Nat. Steir Mark, 44, 195 (1909).
13. Bennewitz, Zentr. Biochem. Biophys., 12, 772 (1912).
14. Besson, Comp. Rend., 147, 848 (1908).
15. Boltwood, Am. J. Sci., 168, 18 (1904).
16. Boltwood, Am. J. Sci., 168, 47 (1904).
17. Boltwood, Am. J. Sci., 168, 97 (1904).
18. Boltwood, Am. J. Sci., 170, 128 (1905).
19. Boltwood and Rutherford, Am. J. Sci., 172, 1 (1906).
20. Boltwood, Am. J. Sci., 175, 269 (1908).
21. Boltwood, Am. J. Sci., 175, 296 (1908).
22. Boltwood, Int. Cong. Rad., Vol. 1 (1910).
23. Brag, Studies in Radioactivity (1912).
24. Brochet, Comp. Rend., 150, 291 (1910).
25. Bronson, Am. J. Sci., 169, 185 (1905).
26. Bumstead and Wheeler, Am. J. Sci., 166, 328 (1903).
27. Cameron, Radium and Radioactivity, p. 18 (1912).
28. Crooks, Proc. Roy. Soc., 71, 405 (1903).
29. Curie and Laborde, Comp. Rend., 138, 1150 (1904).
30. Dame and Cremien, Comp. Rend., 153, 870 (1912).
31. Dienert and Bouquet, Comp. Rend., 145, 894 (1908).
32. Duane and Laborde, Radium, 11, 5 (1914).

Am. Phys., 38, 959 (1912).

Comp. Rend. 150, 1421 (1910).
J. Phys., 4, 605 (1905).
33. Ebler, Zeit. Angew. Chem. 21, 737 (1908).
34. Ebler and Flexner, Zeit. Anorg. Chem., 72, 233 (1912).
35. Elstel and Geitel, Phys. Zeit., 4, 439 (1903).
36. Elstel and Geitel, Phys. Zeit., 5, 321 (1904).
37. Elstel and Geitel, Phys. Zeit., 10, 664 (1909).
38. Engler and Sieveking, Zeit. Anorg. Chem., 53, 1 (1907). 39. Engler and Sieveking, Chem. Zeit., 31, 811 (1908).
40. Fresinius and Czapski, Chem. Zeit., 35, 722 (1912).
41. Garrigon, Comp. Rend., 146, 1352 (1908).
42. Gradenwitz, Rev. Gen. Sci. Pur. and App., 21, 4 (1910).
43. Greinacher, Phys. Zeit., 12, 209 (1911).
44. Greinacher, Phys. Zeit., 13, 435 (1912).
```



```
45. Gudzent, Z. Prak. Geol, 18, 147 (1911).
46. Haywood, U. S. Bur. Chem., Bull. 91.
47. Headden, Am. J. Sci., 169, 297 (1905).
47. Headden, Am. J. Sci., 169, 297 (1905).

48. Henrich, Sitz. K. Akad. Wiss. Wien, 113, 1092.

49. Henrich, Zeit. Anorg. Chem., 65, 714 (1910).

50. Henrich, Zeit. Angew Chem., 23, 340 (1910).

51. Henrich, Zeit. Angew Chem., 23, 1308 (1910).

52. Henrich, Zeit. Angew Chem., 23, 1809 (1910).

53. Henrich, Zeit. Angew Chem., 23, 2125 (1910).

54. Henrich, Erlangen and Glasses, Zeit Angew Chem., 25, 16 (1912).

55. Henrich, Phys. Zeit., 8, 112 (1907).

56. Himstead, Ann. Phys., 13, 573 (1904).

57. Huart and Grechem, Arch. Trim. Luxemburg. Sci., 2, 250 (1907).

58. Ill. Water Survey, Bull. 4, 35 (1908).

59. Jaboin and Beaudoin, Phys. Zeit., 12, 143 (1911).
59. Jaboin and Beaudoin, Phys. Zeit., 12, 143 (1911).
60. Jeutsch, Phys. Zeit., 7, 209 (1906).
61. Jeutsch, Phys. Zeit., 9, 120 (1908).
62. Joly, Radioactivity and Geology (1909).
63. Joly, Phil. Mag., 14, 742 (1907).
64. Joly, Phil. Mag., 15, 385 (1908).
65. Koch, Radium 3, 362.
66. Koch, Phys. Zeit., 7, 806 (1906).
67. LaGrange, Phys. Zeit., 10, 543 (1909).
68. Levin, Phyz. Zeit., 11, 322 (1910).
69. Lind and Whittemore, Bur. Mines Tech. Paper 88 (1915).
70. Loewenthal, Phys. Zeit., 12, 143 (1911).
71. Lutz, Phys. Zeit., 9, 100 (1908).
72. Mache, Phys. Zeit., 5, 441 (1904).
73. Mache and Meyer, Zeit. Instru. 29, (1909).
74. Mache and Meyer, Sitz. K. Akad. Wiss. Wien, 114, 355.
75. Makower, Radioactive Substances, (1908).
76. Massol, Comp. Rend., 155, 373 (1912).
77. McCoy, Ber. Chem. Ges. No. 11, 2641 (1904).
78. McCoy, J. Am. Chem. Soc., 27, 391 (1905). 79. McCoy, Phil. Mag., 11, 177 (1906).
80. McCoy, Ashman and Ross, Am. J. Sci., 176, 521 (1908).

J. Am. Chem. Soc., 29, 1698 (1907).

81. Mezernitsky, J. Russ. Phys. Chem. Soc., 43, 244 (1911).

82. Moore and Schlundt, Trans. Am. Elect. Chem. Soc., 8,291 (1905).

83. Moore and Schlundt, U.S. Geol. Sur., Bull. 395 (1909).

84. Moore and Whittemore, J. Ind. Eng. Chem., 6, 552 (1914).

85. Moreau and Lepane Comp. Rend., 148, 834 (1909).
 85. Moreau and Lepape, Comp. Rend., 148, 834 (1909).
86. Muller, Phys. Zeit., 11, 545 (1910).
87. Olie, Chem. Weekblad, 5, 823, (1908).
88. Peale, U. S. Geol. Sur. Report 14, 66 (1894).
 89. Perkins, Science, 42, 808 (1915).
90. Rafferty, Science of Radioactivity (1909).
 91. Ramsey, Am. J. Sci., 190, 309 (1915).
 92. Randall, Trans. Am. Elect. Chem. Soc., 21, 463 (1912).
93. Repin, Comp. Rend., 147, 387 (1908).
 94. Rutherford, Radioactive Measurements.
95. Rutherford, Radium Transformations.
```

.

96. Rutherford, Radioactive Substances and their Transformations. 97. Rutherford, Ibid. p. 24 (1913). 98. Rutherford, Ibid. p. 50. 99. Rutherford, Ibid. p. 164. 100. Rutherford, Ibid. p. 297. 101. Rutherford, Ibid. p. 460. 102. Rutherford, Ibid. p. 668.
103. Rutherford, Conductance of Electricity Through Gases. 104. Rutherford and McClurg, Phil. Trans. A., 196, 52 (1901). 105. Sarasin, Guye and Mitchell, Arch. Sci. Phy. Nat., 25, 36 (1908) 106. Schlundt and Moore, Am. J. Sci., 168, 97 (1904). 107. Schlundt and Moore, Bur. Mines Tech. Paper, 88, (1915). 108. Schmidt, Phys. Zeit. 8, 107 (1907). 109. Schweitzer, Arh. Sci. Phy. Nat., (4) 27, 256 (1909). 110. Schweitzer, Arh. Sci. Phy. Nat., (4) 30, 46 (1911).
111. Shrader, Phys. Rev., 38, 339 (1914). 112. Sjorgen and Sahlborn, Ark. Kemi. Min. Geol. 3, No. 2 (1908). 113. Soddy, Chem. Radio Elements (1914). 114. Soddy, Radioactivity (1904). 114. Soddy, Radioactivity (1504).

115. Strutt, Proc. Roy. Soc., 73, 191 (1904).

116. Strutt, Nature, March 17, July 17 (1904).

117. Stuttgart, Phy. Zeit., 7, 806 (1906).

118. Szilard, Comp. Rend., 154, 982 (1912).

119. Thomson. Phil. Mag. 47, 253 (1899).

120. Thomson, Proc. Camb. Phil. Soc., 12, 172 (1903). Nature, 67, 609 (1903). 121. Van Hofer, Int. Z. Wass. Versors., 1, 52 (1914). 122. Van Sury, Chem. Zent., 1, 1283 (1907). 123. Wellik, Monatsch, 30, 89 (1909). Mitt. Nat. Steirmark, 45, 257 (1910).

124. Weszelsky, Ion. 2, 388 (1911).

125. Wilson, Proc. Roy. Soc., 68, 152 (1901).

126. Wulf, Phys. Zeit., 9, 1090 (1910).

127. Zeleny, Phy. Rev., 32, 581 (1912).



#### BIOGRAPHY.

The writer received his early education in the public schools of Kissimmee, Florida, and Watseka, Illinois. He was graduated with the degree of Bachelor of Science from the University of Illinois in 1913. In 1914, he received the degree of Master of Science at the same institution.

From 1911 to 1913 he was student assistant in Sanitary Chemistry at the University of Illinois. From 1913 to 1914 he was a graduate assistant in Electro-Chemistry (one semester) and Qualitative Analysis (one semester). During the summers of 1911, 1912, 1913, and 1914 he was assistant chemist in the State Water Survey. From 1914 to 1916 he was a fellow in Sanitary Chemistry at the University of Illinois.

### His publications are:

The Perchloric Method of Determining Potassium as Applied to Water Analysis.

Am. Chem. Soc., 36, 2085 (1914).

Univ. of Ill. Bull., State Water Survey Series No. 11, 150 (1914).

Chem. News, 111, 62 (1915).

#### With Edward Bartow

The Comparative Value of a Calcium Lime and a Magnesium-Calcium Lime for Water Softening.


J. Ind. Eng. Chem., 6, 189 (1914).

Univ. of Ill. Bull., State Water Survey Series No. 11, 142 (1914).



The foregoing investigation was carried out at the suggestion and under the direction of Professor Edward Bartow. I wish to take this opportunity of thanking Professor Bartow for the assistance given me during the investigation. I wish also to express my appreciation of thanks to the members of the Physics Department for their suggestions and help in the electrical measurements.







Simple Electroscope
For Solids



Simple Electroscope For Gases




Simple Electroscope For Solutions



Electroscope For Solids





Apparatus for separating Emanation from Uraninite

Apparatus for separating Emanation from Water

